

Safety Data Sheet

according to UK REACH Regulation

LDS Mortar and Cement

Date: 25.02.2015

Revision date: 20.01.2023

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LDS Mortar and Cement (SL 525)

Further trade names / Item numbers

LDS CP 200, CP 201, DS 271, DS 272, LS 225, NG 511, NG 512, PC 221, PC 222, RM 202, RM 203, RM 204, RM 205, RM 208, RM 210, RM 224, SC 240, SC 241, SC 244, SC 245, SC 250, SC 252, SC 253, SL 501, SL 502, SL 503, SL 505, SL 506, SL 507, SL 525, SR 207, WP 100, WP 101, WP 120 (A-Komp. Pulver)

UFI (EU): DAPE-0SNK-7FCA-P2VQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Building material

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: LDS Construct
Street: Rozieresesteeweg 87 3090
Place: Overijse
Telephone: +32 474 94 49 57
e-mail: info@ldsconstruct.com http://
Internet: www.ldsconstruct.com/
Responsible Department: QM / QS

1.4. Emergency telephone number:

+32 70 245 245

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Irrit. 2; H315
Eye Dam. 1; H318
STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

portland cement
CSA clinker

Signal word: Danger

Pictograms:



Safety Data Sheet

according to UK REACH Regulation

LDS Mortar and Cement

Date: 25.02.2015

Revision date: 20.01.2023

Page 2 of 10

Hazard statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Precautionary statements

P261 Avoid breathing dust.
P280 Wear protective gloves/protective clothing/eye protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352 IF ON SKIN: Wash with plenty of water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If the product is available for everybody, additionally:

P102 Keep out of reach of children.
P501 Dispose of waste according to applicable legislation.

2.3. Other hazards

Product contains chromate reducing agent. As a result, the cement/binder contains less than 2 ppm of water-soluble Chromium-VI. If the storage conditions are not appropriate (exposure to humidity) or the storage period is exceeded, the effectiveness of the present reducing agent can diminish prematurely, and the cement/binder can become skin sensitizing (H317 or EUH203, respectively).
Monitoring procedure e.g. DIN EN 196-10

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Cement, binder, aggregates (sand, chalk), flux agents, additives

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
65997-15-1	portland cement			< 20 %
	266-043-4			
	Skin Irrit. 2, Eye Dam. 1, STOT SE 3; H315 H318 H335			
65997-15-1	calcium sulfoaluminate clinker (CSA clinker)			< 15 %
	934-133-9			
	Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, STOT SE 3; H315 H318 H317 H335			
14808-60-7	Quartz (SiO ₂),			12.5 – 64.2 %
	238-878-4			
	Occupational exposure limit value according to Directive 2000/39/EC			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
65997-15-1	266-043-4	portland cement	< 20 %
		dermal: LD50 ≥ 2000 mg/kg	

Further Information

Portland cement, CSA clinker, Quartz are, according to Art. 2.7 (b) and Annex V.10 of Regulation (EC) No. 1907/2006 (REACH), exempt from the registration requirement.

Safety Data Sheet

according to UK REACH Regulation

LDS Mortar and Cement

Date: 25.02.2015

Revision date: 20.01.2023

Page 3 of 10

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.
The product develops an alkaline pH value with moisture and can cause irritation.

After inhalation

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Wash with plenty of water/soap. In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist. Do not rub eyes.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a doctor if you feel unwell.
If medical advice is needed, have product container or label at hand.

4.2. Most important symptoms and effects, both acute and delayed

May damage the eye-cornea. Irritation to respiratory tract, skin, mucosa may occur. May cause dermatitis.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder, carbon dioxide, foam, water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Non-flammable. Not combustible

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress dust with water spray jet. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Avoid dust formation. Do not breathe dust. Avoid contact with skin, eyes and clothes.
Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For cleaning up

Avoid dust formation. Take up mechanically. For cleaning, approved industrial vacuum cleaners are recommended,
Treat the recovered material as prescribed in the section on waste disposal.

Other information

Provide adequate ventilation. Clean contaminated articles and floor according to the environmental legislation.

Safety Data Sheet

according to UK REACH Regulation

LDS Mortar and Cement

Date: 25.02.2015

Revision date: 20.01.2023

Page 4 of 10

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid dust formation. Do not breathe dust.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Provide adequate ventilation.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

Storage temperature: 5 - 25°C

7.3. Specific end use(s)

Cement

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
1317-65-3	calcium carbonate (limestone), inhalable dust	-	10		TWA (8 h)	WEL
1317-65-3	calcium carbonate (limestone), respirable dust	-	4		TWA (8 h)	WEL
65997-15-1	Portland cement, CSA-clinker, inhalable dust	-	10		TWA (8 h)	WEL
65997-15-1	Portland cement, CSA-clinker, respirable dust	-	4		TWA (8 h)	WEL
14808-60-7	Silica, crystalline, respirable dust	-	0.1		TWA (8 h)	EU

DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route		Effect	Value
471-34-1	calcium carbonate			
Worker DNEL, long-term	inhalation		local	6.36 mg/m ³
Consumer DNEL, long-term	inhalation		local	1.06 mg/m ³
Consumer DNEL, long-term	oral		systemic	6.1 mg/kg bw/day
Consumer DNEL, acute	oral		systemic	6.1 mg/kg bw/day

Safety Data Sheet

according to UK REACH Regulation

LDS Mortar and Cement

Date: 25.02.2015

Revision date: 20.01.2023

Page 5 of 10

PNEC values

CAS No	Substance	
Environmental compartment		Value
471-34-1	calcium carbonate	
Micro-organisms in sewage treatment plants (STP)		100 mg/l

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses according to EN 166

Hand protection

Tested protective gloves must be worn (EN 374)

Material: alkali-resistant, abrasion resistant, waterproof

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Particle filter device (DIN EN 149) recommended

Environmental exposure controls

Water: An increase in pH value is possible through exposure. At a pH value above 9, ecotoxicological effects may occur.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid: Powder
Colour:	grey
Odour:	odourless
Melting point/freezing point:	> 1000 °C
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	not applicable
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value (at 20 °C):	11-13.5 (water-solid ratio = 1:2)
Water solubility: (at 20 °C)	reacts with water
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined

Safety Data Sheet

according to UK REACH Regulation

LDS Mortar and Cement

Date: 25.02.2015

Revision date: 20.01.2023

Page 6 of 10

Density (at 20 °C): 2.75-3.2 g/cm³
 Bulk density (at 20 °C): 0.9-1.5 kg/m³
 Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not explosive.

Oxidizing properties

The product is not oxidising.

Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

Further Information

Average particle size: 5 - 30 µm

SECTION 10: Stability and reactivity

10.1. Reactivity

Contact with water liberates silicate hydrate and calcium hydroxide.

After curing no reactivity

10.2. Chemical stability

The product is stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Humidity, water

10.5. Incompatible materials

Acids, ammonium salts, aluminum or other base metals

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
65997-15-1	portland cement				
	dermal	LD50 mg/kg	> 2000	Rabbit	Manufacturer limit test

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

LDS Mortar and Cement

Date: 25.02.2015

Revision date: 20.01.2023

Page 7 of 10

STOT-single exposure

May cause respiratory irritation. (portland cement, CSA clinker)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

Other information

The product develops an alkaline pH value with moisture and can cause irritation.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not ecotoxic.

12.2. Persistence and degradability

The product is inorganic. The methods for determining the biological degradability are not applicable to inorganic substances. After curing, the cement has no toxicity

12.3. Bioaccumulative potential

Not applicable. Product is inorganic.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Allow product to harden, then dispose of as construction waste.

List of Wastes Code - residues/unused products

101306 WASTES FROM THERMAL PROCESSES; wastes from manufacture of cement, lime and plaster and articles and products made from them; particulates and dust (except 10 13 12 and 10 13 13)

List of Wastes Code - contaminated packaging

150105 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); composite packaging

Contaminated packaging

Completely emptied packages can be recycled.

Safety Data Sheet

according to UK REACH Regulation

LDS Mortar and Cement

Date: 25.02.2015

Revision date: 20.01.2023

Page 8 of 10

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 47: not applicable

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Additional information

No restriction according to REACH, mixture does not contain SVHC $\geq 0.1\%$ (w/w)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Revised due to Directive (EU) No 2020/878

Safety Data Sheet

according to UK REACH Regulation

LDS Mortar and Cement

Date: 25.02.2015

Revision date: 20.01.2023

Page 9 of 10

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
UVCB: Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

Safety Data Sheet

according to UK REACH Regulation

LDS Mortar and Cement

Date: 25.02.2015

Revision date: 20.01.2023

Page 10 of 10

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Products containing cement, low in chromate	PW, C	-	9b	-	-	-	-	cement

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)